SONY

Contactless IC Chip

RC-S966



* The image printed on this card is only a sample.

The FeliCa™ Lite-S: RC-S966 product is a small-size contactless IC chip with streamlined security function and an optimized file system. FeliCa Lite-S can be used for any NFC Forum Type 3 Tag solution, such as handover connection and smart poster, in combination with any NFC device.



FEATURES

Mutual authentication utilizing MAC¹⁾

FeliCa Lite-S has read-access control and write-access control functionality due to the use of MAC to prevent any unauthorized access. The function to generate a MAC on FeliCa Lite-S makes it possible to carry out streamlined mutual authentication between the product and the reader, supporting secure application development.

1) MAC: Message Authentication Code

NFC Forum Type 3 Tag

FeliCa Lite-S supports Type 3 Tag operation, as defined by the NFC Forum. Therefore, the chip can communicate with standard NFC smartphones and readers. The user memory of 224 bytes is sufficient for most NFC-tag applications and usages.

Several access attributes on a simple file system

The chip uses a simple file structure that has no hierarchical structure. It supports the following access attributes for each user block separately.

- Read Only Access
- Read / Write Access
- Read After Authentication
- Write After Authentication
- Write With MAC

Fast transaction speed

The RC-S966 product supports simultaneous 64-byte data-read and simultaneous 16-byte data-write operations, together with a 212 / 424 kbps data-transfer rate.

Anti-tearing transaction function and data integrity-check function

FeliCa Lite-S has anti-tearing transaction functionality to prevent incomplete data update. Even if a data error occurs in the chip, there is CRC data check code for every data block (16 bytes), so the data error can be detected.

A software development kit, SDK for NFC, is available

Software development kit SDK for NFC is available to develop applications for FeliCa Lite-S and Sony NFC readers. The technical documents of FeliCa Lite-S for application development are also downloadable from the Technical Information website.

APPLICATIONS

NFC handover	ID	Loyalty program
Bluetooth®, Wi-Fi, etc	Company ID, Student card, etc	Loyalty points, Gift card

Transportation	Entertainment
Single-journey ticket	Event ticket, Game card


PRODUCT SPECIFICATIONS

	RC-S966	
Communication method	Conforms to ISO/IEC 18092 (212 kbps / 424 kbps passive communication mode)	
Operating frequency / Modulation / Bit coding	13.56 MHz / ASK modulation / Manchester encoding system	
Communication speed	Supports automatic 212 / 424 kbps switching	
Memory size	14 blocks + 1 subtraction block (1 block = 16 bytes)	
System Separation	No	
Authentication method between card and reader / writer	Streamlined mutual authentication 1) with T-DES	
Channel encryption	No	
Read access control	Yes	
Write access control	Yes	
Supported commands	Non encryption commands (Polling, Read Without Encryption, Write Without Encryption)	
Operating temperature	-25 °C to +100 °C (Quality and reliability are assured when the operating temperature is within the range of -25 °C to +85 °C.)	
Storage temperature	-55 ℃ to +125 ℃	

¹⁾ Different from mutual authentication used for FeliCa Standard IC chip

For technical documents about this product, see "Technical Information" on the FeliCa website: sony.co.jp/en/Products/felica/business/tech-support/

TYPICAL SYSTEM LAYOUT



- · Features, design, and specifications are subject to change without notice.
- SONY and FeliCa are registered trademarks or trademarks of Sony Group Corporation or its affiliates. FeliCa is a contactless IC card technology developed by Sony Corporation.
- The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Sony Corporation is under license.
 All other trademarks are the property of their respective owners.

Sony Corporation

Secure Technology Business Division **Enterprise Solutions Business Unit**

Sony City Osaki 2-10-1 Osaki Shinagawa-ku, Tokyo, 141-8610 Japan